## Panel Saws

Designed for use on panel machines for cutting MDF, particle board, laminates, and bonded materials. All Panel Saws are made with SuperMicro-Sheen C-11 sub-micron carbide for longer life. Machine applications listed are only a guideline. All Panel Saws have a 10 degree hook angle.

DIA COR	TDDTT	DODE 4	MEDE	DI ATT	DECTOR	ODDED III	POR LINE OLD
DIAMTER mm	TEETH	BORE & PINHOLE mm	KERF	PLATE mm	DESIGN	ORDER ID	FOR USE ON
300	60T	30	4.4	3.2	TCG	PS3003060T	Mayer, Scheer
300	60T	80	4.4	3.2	TCG	PS3008060T	Mayer, Scheer
300	70 <b>T</b>	30	3.2	2.2	ATB	GAM3003072	Altendorf, Scheer
300	96T	30	3.2	2.2	ATB	GAM3003096	Altendorf, Scheer
320	72 <b>T</b>	50	4.4	3.2	TCG	PS3205072T	Giden
350	54T	30	4.4	3.2	ATB	PS3503054A	Mayer, SCMI
350	54T	30	4.4	3.2	TCG	PS3503054T	SCMI
350	72T	30	4.4	3.2	ATB	PS3503072A	SCMI
350	72 <b>T</b>	30	4.4	3.2	TCG	PS3503072T	SCMI
350	72 <b>T</b>	1-1/4	4.4	3.2	TCG	PS350Q72T	SCMI
350	54T	75	4.4	3.2	ATB	P83507554A	Giden, Homag
350	72T	75	4.4	3.2	TCG	PS3507572T	Giden, Homag
350	72T	80, 4/9/100 + 2/7/110 + 2/14/110	4.4	3.2	TCG	PS3508072T	SCM,Gabbiani Gabbiani
370	72 <b>T</b>	30,2/10/60	4.4	3.2	TCG	PS3703072T	Shelling
380	60T	60, 2/14/100	4.4	3.2	TCG	PS3806060T	Holzma
380	72 <b>T</b>	60, 2/14/100	4.4	3.2	TCG	PS3806072T	Holzma
380	72T	60, 2/14/100	4.8	3.4	TCG	PS38060T2B	Holzma
400	72 <b>T</b>	30	4.4	3.2	TCG	PS4003072T	Shelling
400	60T	75	4.4	3.2	TCG	PS4007560T	Giden, Homag
400	72 <b>T</b>	60/2/14/100	4.4	3.2	TCG	PS4006072T	Holzma
400	60T	80,/2/9/130+ 4/19/120	4.4	3.2	TCG	PS4008060T	Selco
400	72T	80, 4/9/100+	4.4	3.2	TCG	PS4008072T	Gabbiani

## Panel Saws - Alternate Top(cont.)

DIAMTER	TEETH	BORE &	KERF	PLATE	DESIGN	ORDER ID	FOR USE
mm		PINHOLE mm	mm	mm			ON
420	72T	60, 2/14/100	4.8	3.4	TCG	PS4206072T	Holzma
430	72T	80, 2/9/130/ + 4/19/120	4.4	3.2	ATB	PS4308072T	Selco
450	72T	60, 2/14/125	4.8	3.4	TCG	PS4506072T	Holzma
450	72T	80, 2/19/130+ 4/9/120	4.4	3.2	ATB	PS4508072A	Selco
450	72T	80, 2/19/130+ 4/9/120	4.4	3.2	TCG	PS4508072T	Selco
460	72T	30, 2/7/110+ 2/14/110	4.4	3.2	TCG	PS4603072T	Holzma
480	60T	30	4.4	3.2	TCG	PS4803060T	Shelling
480	72T	30	4.4	3.2	TCG	PS4803072T	Shelling
480	72T	80,2/9/130+ 4/9/120	4.8	3.5	TCG	PS4808072T	Selco
500	72T	60, 2/11/115+ 2/19/120	5	3.5	TCG	PS5006072T	Holzma
500	72T	75,2/11/115+2 /19/120	5	3.5	TCG	PS5007572T	Giden
500	72T	80, 2/19/110	5	3.5	TCG	PS5008072T	Gabbiani
520	60T	60, 2/11/115	4.8	3.5	TCG	PS5206060T	Holzma
530	60T	30	5	3.5	TCG	PS5303060T	Shelling
540	60T	60, 2/11/115+ 2/19/120	5	3.5	TCG	PS5406060T	Holzma
540	84T	60,2/11/115+2 /19/120	5	3.5	TCG	PS5406084T	Holzma
550	72T	100	5	3.5	TCG	PS5501072TG	Giden
570	60T	60,2/11/115+2 /19/120	5	3.5	TCG	PS5706060T	Holzma
600	60T	60,2/11/115+2 /19/120	5.8	4	TCG	PS6006060T	Holzma